



SL1 RC

SRAM

Sizes	(XS)44, (S)47, (M)50, (M/L)53, (L)55, (XL)58
Color(s)	White/Carbon
Main frame	C-10 SuperLite Monocoque High Modulus carbon with 3K, Integrated aluminum cupped head tube, Double water bottle mounts
Rear triangle	C-10 SuperLite High Modulus carbon stays with shaped ride tuned Energy Transfer Chainstay, cold forged dropout with replaceable hanger
Fork	Fuji FC-330 Carbon Monocoque Integrated 1 1/8" Carbon steerer, 350g
Crankset	SRAM RED Hollow Carbon w/ Integrated Spindle, Standard 39/53T
Bottom bracket	SRAM Exterior Bearing system
Pedals	Nil
Front derailleur	SRAM RED Braze-on Type
Rear derailleur	SRAM RED
Shifters	SRAM RED Double Tap shifter/brake, 20-speed
Cassette	SRAM RED, 11-26T 10-speed,
Chain	SRAM PC-1090, 10-speed
Wheelset	Reynold Assault DV, 700c carbon clincher
Tires	Vittoria Diamante Pro, 700 X 23c
Tubes	Kenda Ultralite presta tubes
Brake set	SRAM RED dual pivot w/cartridge pads
Brake levers	SRAM RED Double Tap
Headset	Cane Creek IS-81 1 1/8" Integrated Road, with Carbon convex topcap and InterLoc spacers
Handlebar	Ritchey WCS EVO Carbon 31.8mm Road
Stem	Ritchey WCS 4Axis Carbon Alloy Matrix, +/-6 degree
Tape/grip	Fuji Custom Micro-fibre wrap
Saddle	Prologoo C.ONE50-Ti Carbon base w/Hollow Ti rail
Seat post	Ritchey Carbon WCS Oversize 1-Bolt, 300mm
Seat clamp	Fuji Superlite Alloy, 34.9mm Laser Etched
Other	7075 alloy water bottle bolts
Weight, kg./lb.	6.64kg / 14.63lbs

- Fuji's carbon race ultralight @ 14.5 lbs (6.6 kg)
- Available with SRAM Red or Shimano Dura Ace 7900 components
- Also available as a frameset



SIZE	XS	S	M	M/L	L	XL
SEAT TUBE, C TO T	440.0	470.0	500.0	530.0	550.0	580.0
EFFECTIVE TT LENGTH	510.0	524.9	545.0	555.2	570.0	600.0
CHAIN STAY	405.0	405.0	405.0	405.0	405.0	405.0
HEAD TUBE ANGLE	70.0	71.0	71.5	72.0	72.0	72.0
SEAT TUBE ANGLE	75.0	74.5	73.5	73.5	73.5	73.5
WHEEL BASE	976.5	980.0	987.6	994.0	1000.1	1039.4
STAND OVER HEIGHT	714.2	734.3	758.8	783.0	798.8	817.1
HEAD TUBE LENGTH	110.0	120.0	140.0	160.0	170.0	180.0
REACH	371.0	379.0	384.7	389.0	400.0	428.0
STACK	502.0	515.0	536.5	557.0	570.0	576.0
STEM LENGTH	90.0	100.0	110.0	120.0	120.0	130.0
HANDLEBAR WIDTH	380.0	400.0	400.0	420.0	420.0	440.0
CRANK LENGTH	165.0	170.0	170.0	172.5	172.5	175.0

NOTES: